

**SPECIFICATIONS – power amplifier IRNI-L DL 1000**

Amplifier	<b>DL 1000</b>	
<i>Load impedance, ohms</i>	<b>4</b>	<b>8</b>
<i>Max. Output Power, Dual Channel, 1 KHz, watts</i>	500	330
<i>Input Sensitivity, V</i>	0.775	
<i>THD, 1kHz</i>	< 0,02 %	
<i>Frequency response</i>	15Hz – 25 KHz	
<i>Input Impedance</i>	20 kohm	
<i>Damping Factor, 1Khz</i>	>300	
<i>Slew rate</i>	45V / $\mu$ s	
<i>Signal to Noise Ratio</i>	105,0 dB	
<i>Efficiency :</i>	> 92%	
<i>Power Consumption, max</i>	1200 W	
<i>Output stage technology</i>	Class <b>D</b>	
<i>Cooling</i>	2 fans, front to rear	
<i>Protection</i>	High temperature, DC, HF, Turn on delay, Short circuit	
<i>Connectors:</i>	Input - 1/4" TRS ,Output - SPEAKON	
<i>Indicators:</i>	Power, Protect, Peak	
<i>Dimensions, mm</i>	483 x 44 x 237	
<i>Weight</i>	8,7 kg	